

CONNECTORS

Part Number	Description
ANO 2511-2020	3.5mm Straight Male Solder For IW1501/PLEX-140 Cable
ANO 2511-2038	3.5mm Straight Male Solder For .141 Cable, Solder Direct
ANO 2512-2021	3.5mm Straight Female Solder For IW1501/PLEX-140 Cable, Captivated Contact
ANO 2512-2039	3.5mm Straight Female Solder For .141 Cable, Solder Direct
ANO 2921-2161	2.92mm Right Angle Male Solder for .141 Cable, Captivated Contact
ANO 7111-2005	NMD3.5mm Straight Male Solder For IW1501/PLEX-140 Cable
ANO 7112-2006	NMD3.5mm Straight Female Solder For IW1501/PLEX-140 Cable, Captivated Contact
ANO 2912-2131	2.92mm Straight Female Solder for AFLEX-141 Cable Captivated Contact
ANO 9111-2047	SSMA Straight Male Solder for .086 Cable

ADAPTERS

Part Number	Description
PA2525A	Precision Adapter 3.5mm Male To 3.5mm Male
PA2525B	Precision Adapter 3.5mm Male To 3.5mm Female
PA2525C	Precision Adapter 3.5mm Female To 3.5mm Female
PA2525E	Precision Adapter, 3.5mm Female Bulkhead To 3.5mm Female
PA2525F	Precision Adapter 3.5mm Female To 3.5mm Female 4 Hole Flange
PA6225A	Precision Adapter 1.85mm Male To 3.5mm Male
PA6225B	Precision Adapter 1.85mm Male To 3.5mm Female
PA6225C	Precision Adapter 1.85mm Female To 3.5mm Female
PA6225D	Precision Adapter 1.85mm Female To 3.5mm Male
PA2225A	Precision Adapter 2.4mm Male To 3.5mm Male
PA2225B	Precision Adapter 2.4mm Male To 3.5mm Female
PA2225C	Precision Adapter 2.4mm Female To 3.5mm Female
PA2225D	Precision Adapter 2.4mm Female To 3.5mm Male
PA2925A	Precision Adapter, 2.92mm Male to 3.5mm Male
PA2925B	Precision Adapter, 2.92mm Male To 3.5mm Female
PA2925C	Precision Adapter, 2.92mm Female To 3.5mm Female

30-34 GHz Products



[PA2925D](#) Precision Adapter, 2.92mm Female To 3.5mm Male

[PA2925F](#) Precision Adapter, 2.92mm Female To 3.5mm Female 4 Hole Flange

[PA2525EB](#) PRECISION ADAPTER, 3.5MM FEMALE BULKHEAD TO 3.5MM FEMALE

[PA2525EA](#) Precision Adapter, 3.5mm Female Bulkhead to 3.5mm Female

CABLES

Part Number	Description
-------------	-------------

[AFLEX-141](#) AFLEX Series Cable, AFLEX-141 with FEP Jacket

TERMINATIONS

Part Number	Description
-------------	-------------

[ANO 725-106](#) Coaxial Termination With Chain 3.5mm Male, 1 Watt, DC-33 GHz

[ANO 791-101](#) Coaxial Termination, SSMA Male, 1 Watt, DC-33 GHz

ATTENUATORS

Part Number	Description
-------------	-------------

[ANO 25-5001-06](#) 6 dB Attenuator, 3.5mm Male to 3.5mm Female, 50 Watts, DC-30 GHz

[ANO 25-5001-10](#) 10 dB Attenuator, 3.5mm Male to 3.5mm Female, 50 Watts, DC-30 GHz

[ANO 25-5001-20](#) 20 dB Attenuator, 3.5mm Male to 3.5mm Female, 50 Watts, DC-30 GHz

[ANO 25-5001-30](#) 30 dB Attenuator, 3.5mm Male to 3.5mm Female, 50 Watts, DC-30 GHz

[ANO 25-5001-40](#) 40 dB Attenuator, 3.5mm Male to 3.5mm Female, 50 Watts, DC-30 GHz

[ANO 25-10001-10](#) 10 dB Attenuator, 3.5mm Male to 3.5mm Female, 100 Watt, DC-31 GHz

[ANO 25-10001-20](#) 20 dB Attenuator, 3.5mm Male to 3.5mm Female, 100 Watt, DC-31 GHz

[ANO 25-10001-30](#) 30 dB Attenuator, 3.5mm Male to 3.5mm Female, 100 Watt, DC-31 GHz

[ANO 25-10001-40](#) 40 dB Attenuator, 3.5mm Male to 3.5mm Female, 100 Watt, DC-31 GHz

[ANO 25-1001-01](#) 1 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz

[ANO 25-1001-02](#) 2 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz

[ANO 25-1001-03](#) 3 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz

[ANO 25-1001-04](#) 4 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz

[ANO 25-1001-05](#) 5 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz

[ANO 25-1001-06](#) 6 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz

[ANO 25-1001-07](#) 7 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz

30-34 GHz Products



ANO 25-1001-08	8 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz
ANO 25-1001-09	9 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz
ANO 25-1001-10	10 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz
ANO 25-1001-15	15 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz
ANO 25-1001-20	20 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz
ANO 25-1001-25	25 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz
ANO 25-1001-30	30 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz
ANO 25-1001-35	35 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz
ANO 25-1001-40	40 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz
ANO 29-0209-01	1dB Attenuator, 2.92mm Male to 2.92 Female, 2 Watts, DC-32 GHz
ANO 29-0209-02	2 dB Attenuator, 2.92mm Male to 2.92 Female, 2 Watts, DC-32 GHz
ANO 29-0209-03	3 dB Attenuator, 2.92mm Male to 2.92 Female, 2 Watts, DC-32 GHz
ANO 29-0209-04	4 dB Attenuator, 2.92mm Male to 2.92 Female, 2 Watts, DC-32 GHz
ANO 29-0209-05	5 dB Attenuator, 2.92mm Male to 2.92 Female, 2 Watts, DC-32 GHz
ANO 29-0209-06	6 dB Attenuator, 2.92mm Male to 2.92 Female, 2 Watts, DC-32 GHz
ANO 29-0209-07	7 dB Attenuator, 2.92mm Male to 2.92 Female, 2 Watts, DC-32 GHz
ANO 29-0209-08	8 dB Attenuator, 2.92mm Male to 2.92 Female, 2 Watts, DC-32 GHz
ANO 29-0209-09	9 dB Attenuator, 2.92mm Male to 2.92 Female, 2 Watts, DC-32 GHz
ANO 29-0209-10	10 dB Attenuator, 2.92mm Male to 2.92 Female, 2 Watts, DC-32 GHz
ANO 29-0209-20	20 dB Attenuator, 2.92mm Male to 2.92 Female, 2 Watts, DC-32 GHz
ANO 29-0209-30	30 dB Attenuator, 2.92mm Male to 2.92 Female, 2 Watts, DC-32 GHz
ANO 29-0209-40	40 dB Attenuator, 2.92mm Male to 2.92 Female, 2 Watts, DC-32 GHz
ANO 25-0201-31	31 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0201-32	32 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0201-33	33 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0201-34	34 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0201-35	35 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0201-36	36 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0201-37	37 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz

30-34 GHz Products



ANO 25-0201-38	38 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0201-39	39 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0201-40	40 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-01	1 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-02	2 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-03	3 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-04	4 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-05	5 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-06	6 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-07	7 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-08	8 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-09	9 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-10	10 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-15	15 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-20	20 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-25	25 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-30	30 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-35	35 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-40	40 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz

TOOLS

Part Number	Description
ANO TW-001	Torque Wrench for SMA/3.5 mm/2.92 mm/2.4 mm/1.85 mm Type Connectors, Preset Torque= 8 ± 0.32 in.lbs, Hex Size =5/16 in.
ANO TW-002	Torque Wrench for SMA/3.5 mm/2.92 mm/2.4 mm/1.85mm Type Connectors, Preset Torque= 12 ± 0.48 in.lbs, Hex Size =5/16 in.
ANO TWSD-001	Torque Wrench in Screwdriver Type, for SMA /3.5mm /2.92mm /2.4mm /1.85mm Type Connectors, Preset Torque= 0.9 ± 0.04 NM [8 ± 0.32 IN.LBS], Hex Size 7.94 MM [5/16 IN.]
T21003	SMA, 3.5mm 2.92mm, 2.4mm, 1.85mm Connector-Finger Thumb Wrench Blue

ACCESSORIES

Part Number	Description
ANO 2111-6099	Cap, Male With Chain for SMA, 3.5mm, 2.92mm
ANO 251-801	3.5mm Male Short