

CONNECTORS

Product Name	Description
ANO 221-AX-H	2.4mm Male End Launch Connector Standard Profile
ANO 221-AX-L	2.4MM Male End Launch Connector Low Profile
ANO 2211-2003	2.4mm Straight Male Solder For IW1401/PLEX-135 Cable Captivated Contact
ANO 2211-2013	2.4mm Straight Male Solder For PLEX-130P Cable Captivated Contact
ANO 2211-2028	2.4mm Straight Male Solder for PLEX-130P Cable, Captivated Contact
ANO 2211-2033	2.4MM Straight Male Solder For UT-085/UT-085C-Form Cable, Captivated Contact
ANO 2211-2044	2.4mm Straight Male Solder for .047 Cable, Solder Direct
ANO 2211-2070	2.4mm Straight Male Solder for SR070TPLL Cable
ANO 2211-3011-1	2.4mm Straight Male 4 Hole .500" SQ. Flange To Accept .009" Pin Dia., Field Replaceable
ANO 2211-3011-2	2.4mm Straight Male 4 Hole .500" SQ Flange To Accept .012" Pin Dia., Field Replaceable
ANO 2211-3011-3	2.4mm Straight Male 4 Hole .500" SQ. Flange To Accept .020" Pin Dia., Field Replaceable
ANO 2211-3018-1	2.4mm Straight Male 4 Hole .375" SQ. Flange Accept .009" Pin Dia., Field Replaceable
ANO 2211-3018-2	2.4mm Straight Male 4 Hole .375" SQ. Flange Accept .012" Pin Dia., Field Replaceable
ANO 2211-3018-3	2.4mm Straight Male 4 Hole .375" SQ. Flange Accept .020" Pin Dia., Field Replaceable
ANO 2211-3019-1	2.4mm Straight Male 2 Hole .625" Long Flange, Accepts .009" Pin Dia, Field Replaceable
ANO 2211-3019-2	2.4mm Straight Male 2 Hole .625" Long Flange, Accepts .012" Pin Dia, Field Replaceable
ANO 2211-3019-3	2.4mm Straight Male 2 Hole .625" Long Flange, Accepts .020" Pin Dia, Field Replaceable
ANO 2211-3020-1	2.4mm Straight Male 2 Hole .550" Long Flange Accept .009" Pin Dia., Field Replaceable
ANO 2211-3020-2	2.4mm Straight Male 2 Hole .550" Long Flange Accept .012" Pin Dia., Field Replaceable
ANO 2211-3020-3	2.4mm Straight Male 2 Hole .550" Long Flange Accept .020" Pin Dia., Field Replaceable
ANO 2211-3021-1	2.4mm Straight Male 2 Hole .500" Long Flange Accept .009" Pin Dia., Field Replaceable
ANO 2211-3021-2	2.4mm Straight Male 2 Hole .500" Long Flange Accept .012" Pin Dia., Field Replaceable
ANO 2211-3021-3	2.4mm Straight Male 2 Hole .500" Long Flange Accept .020" Pin Dia., Field Replaceable
ANO 2211-3031	2.4mm Stright Male, 2 Hole Flange .550" Long, Flange, Solder Attachment Pin Terminal
ANO 2211-3053	2.4mm Straight Male 4 Hole Flange With Extended Teflon And Blunt Post
ANO 2211-3067	2.4mm Straight Male, 2 Hole Flange Mount, Extended Dielectric, Post Contact
ANO 2212-1026	2.4mm Straight Bulkhead Female Solder for .086 Cable, Captivated Contact

50 GHz Products



ANO 2212-1046	2.4mm Straight Female 2 Hole Flange Mount, Solder for .034 Cable
ANO 2212-2008	2.4mm Straight Female Solder for IW1401 Cable Captivated Contact
ANO 2212-2016	2.4mm Straight Female Solder For PLEX-130P Cable Captivated Contact
ANO 2212-3005-1	2.4mm Female, 2 Hole .622" Long Flange Accept .009" Pin Dia., Field Replaceable
ANO 2212-3005-2	2.4mm Female, 2 Hole .622" Long Flange Accept .012" Pin Dia., Field Replaceable
ANO 2212-3005-3	2.4mm Female, 2 Hole .622" Long Flange Accept .020" Pin Dia., Field Replaceable
ANO 2212-3005-4	2.4mm Female, 2 Hole .622" Long Flange Accept .015" Pin Dia., Field Replaceable
ANO 2212-3005-5	2.4mm Female, 2 Hole .622" Long Flange Accept .018" Pin Dia., Field Replaceable
ANO 2212-3006-1	2.4mm Female, 2 Hole .551" Long Flange Accept .009" Pin Dia., Field Replaceable
ANO 2212-3006-2	2.4mm Female, 2 Hole .551" Long Flange Accept .012" Pin Dia., Field Replaceable
ANO 2212-3006-3	2.4mm Female, 2 Hole .551" Long Flange Accept .020" Pin Dia., Field Replaceable
ANO 2212-3006-4	2.4mm Female, 2 Hole .551" Long Flange Accept .015" Pin Dia., Field Replaceable
ANO 2212-3006-5	2.4mm Female, 2 Hole .551" Long Flange Accept .018" Pin Dia., Field Replaceable
ANO 2212-3009-1	2.4mm Female, 2 Hole .500" Long Flange Accept .009" Pin Dia., Field Replaceable
ANO 2212-3009-2	2.4mm Female, 2 Hole .500" Long Flange Accept .012" Pin Dia., Field Replaceable
ANO 2212-3009-3	2.4mm Female, 2 Hole .500" Long Flange Accept .020" Pin Dia., Field Replaceable
ANO 2212-3009-4	2.4mm Female, 2 Hole .500" Long Flange Accept .015" Pin Dia., Field Replaceable
ANO 2212-3009-5	2.4mm Female, 2 Hole .500" Long Flange Accept .018" Pin Dia., Field Replaceable
ANO 2212-3012-1	2.4mm Female, 4 Hole .375" SQ. Flange, Accept .009" Pin Dia., Field Replaceable
ANO 2212-3012-2	2.4mm Female, 4 Hole .375" SQ. Flange, Accept .012" Pin Dia., Field Replaceable
ANO 2212-3012-3	2.4mm Female, 4 Hole .375" SQ. Flange, Accept .015" Pin Dia., Field Replaceable
ANO 2212-3012-4	2.4mm Female, 4 Hole .375" SQ. Flange, Accept .020" Pin Dia., Field Replaceable
ANO 2212-3015	2.4mm Female, 2 Hole Flange, .480" Hole Spacing, Mount Post Contact
ANO 2212-3017-1	2.4mm Straight Female 4 Hole .500" SQ. Flange Accept .009" Pin Dia., Field Replaceable
ANO 2212-3017-2	2.4mm Straight Female 4 Hole .500" SQ. Flange Accept .012" Pin Dia., Field Replaceable
ANO 2212-3017-3	2.4mm Straight Female 4 Hole .500" SQ. Flange Accept .020" Pin Dia., Field Replaceable
ANO 2212-3024	2.4mm Straight Female 2 Hole .400" Long Flange Mount W/Mouse Hole
ANO 2212-3025	2.4mm Female, 2 Hole .550" Long Flange Mount Post Contact
ANO 2212-3030	2.4mm Female, 4 Hole Flange Mount Post Contact

50 GHz Products



ANO 2212-3049	2.4mm Female, 4 Hole Flange Mount Post Contact
ANO 2212-3054	2.4mm Female, 2 Hole Flange Mount VRT Launch
ANO 2212-3075	2.4mm Female, Vertical Launch Stripline, 2 Hole Flange, Compression Mount
ANO 2212-4032	2.4mm Female PCB Mount, ø.012 Pin
ANO 2212-5010-1	2.4mm Female, Rear Thread-In, Accept .020 Pin Dia., Field Replaceable
ANO 2212-5010-2	2.4mm Female, Rear Thread-In, Accept .012 Pin Dia., Field Replaceable
ANO 2212-5010-3	2.4mm Female, Rear Thread-In, Accept .009 Pin Dia., Field Replaceable
ANO 2212-5010-4	2.4mm Female, Rear Thread-In, Accept .009 Pin Dia., Field Replaceable
ANO 2212-5010-5	2.4mm Female, Rear Thread-In, Accept .015 Pin Dia., Field Replaceable
ANO 2212-5010-6	2.4mm Female, Rear Thread-In, Accept .018 Pin Dia., Field Replaceable
ANO 222-AX-H	2.4mm Female End Launch Connector Standard Profile
ANO 222-AX-L	2.4mm Female End Launch Connector Low Profile
ANO 222-B1	2.4mm Female End Launch Connector Super Small End Launch
ANO 222-C1	2.4mm Female End Launch Connector Super Small End Launch-Wide
ANO 6811-2007	NMD2.4mm Straight Male Solder For PLEX-130P Cable, Captivated Contact
ANO 6812-2008	NMD2.4mm Straight Female Solder For PLEX-130P Cable, Captivated Contact
ANO 9411-5090	SMPM-T Male Edge Launch, Smooth Bore
ANO 9421-2011-1	SMPM R/A Male Full Detent Solder For .086 Cable
ANO 9421-2011-2	SMPM R/A Male Smooth Bore Solder For .086 Cable
ANO 9422-2012	SMPM R/A Female Solder For .086 Cable

ADAPTERS

Product Name	Description
PA2222A	Precision Adapter 2.4mm Male To 2.4mm Male
PA2222B	Precision Adapter 2.4mm Male To 2.4mm Female
PA2222C	Precision Adapter, 2.4mm Female to 2.4mm Female
PA2222E	Precision Adapter 2.4mm Female Bulkhead To 2.4mm Female
PA2222F	Precision Adapter, 2.4mm Female to 2.4mm Female, 2 Hole Flange
PA2222FA	Precision Adapter, 2.4mm Female to 2.4mm Female, 2 Hole Flange
PA2222FC	Precision Adapter, 2.4mm Female to 2.4mm Female, 4 Hole Flange

50 GHz Products



PA6222A	Precision Adapter 1.85mm Male To 2.4 Mm Male
PA6222B	Precision Adapter 1.85mm Male To 2.4mm Female
PA6222C	Precision Adapter 1.85mm Female To 2.4mm Female
PA6222D	Precision Adapter 1.85mm Female To 2.4mm Male
PA6922C	Precision Adapter, NMD1.85mm Female to 2.4mm Female
PA6968D	Precision Adapter, NMD1.85mm Female to NMD2.4mm Male
PA6822C	Precision Adapter, NMD2.4mm Female to 2.4mm Female
PA6868B	Precision Adapter, NMD2.4mm Female to NMD2.4mm Male
PA2222J	Precision Adapter, Right Angle 2.4mm Male to 2.4mm Male
PA2222K	Precision Adapter, Right Angle 2.4mm Male To 2.4mm Female
PA2222L	Precision Adapter, Right Angle 2.4mm Female to 2.4mm Female
PA6822D	Precision Adapter, NMD2.4mm Female to 2.4mm Male
PA6822B	Precision Adapter, NMD2.4mm Male to 2.4mm Female
PA6922CA	Precision Adapter, NMD1.85mm Female to 2.4mm Female
PA6822CA	Precision Adapter, NMD2.4mm Female to 2.4mm Female
PA6222K	Precision Adapter, Right Angle 1.85mm Male to 2.4mm Female
PA6222L	Precision Adapter, Right Angle 1.85mm Female to 2.4mm Female
PA6222M	Precision Adapter, Right Angle 1.85mm Female to 2.4mm Male
PA6222J	Precision Adapter, Right Angle 1.85mm Male to 2.4mm Male

CABLES

Product Name	Description
EP180	EP Series Cable, EP180 with TPU Jacket
MB103	MB Series Cable, MB103 With Blue FEP Jacket
PLEX130P	PLEX Series Cable, PLEX130P With Blue FEP Jacket
PLEX135	PLEX Series Cable, PLEX135 With Gray FEP Jacket
SUPO-125	SUPO Series Cable, SUPO-125 with FEP Jacket
SR086	Semi-Rigid Series Cable, 50 Ohm, with Copper Tube

CABLE ASSEMBLIES

Product Name	Description
--------------	-------------

50 GHz Products



PT-24F-18M-26	Cable Assembly, 2.4mm Female to 1.85mm Male, PT-24 (PT Series Precision Test Cables), 26 Inches
PT-24F-18M-39	Cable Assembly, 2.4mm Female to 1.85mm Male, PT-24 (PT Series Precision Test Cables), 39 Inches
PT-24F-24F-26	Cable Assembly, 2.4mm Female to 2.4mm Female, PT-24 (PT Series Precision Test Cables), 26 Inches
PT-24F-24F-39	Cable Assembly, 2.4mm Female to 2.4mm Female, PT-24 (PT Series Precision Test Cables), 39 Inches
PT-24M-24F-26	Cable Assembly, 2.4mm Male to 2.4mm Female, PT-24 (PT Series Precision Test Cables), 26 Inches
PT-24M-24F-39	Cable Assembly, 2.4mm Male to 2.4mm Female, PT-24 (PT Series Precision Test Cables), 39 Inches
PT-24M-24M-26	Cable Assembly, 2.4mm Male to 2.4mm Male, PT-24 (PT Series Precision Test Cables), 26 Inches
PT-24M-24M-39	Cable Assembly, 2.4mm Male to 2.4mm Male, PT-24 (PT Series Precision Test Cables), 39 Inches
SR086LL-24M-24M-18-PM	Cable Assembly, 2.4mm Straight Male to 2.4mm Straight Male, SR086LL Cable, 18 Inches
SR086TPLL-24F-24M-970MM	Cable Assembly, 2.4mm Straight Female to 2.4mm Straight Male, ANO SR086TP-LL Cable, 0.97 meters
mBend-SMPM(F)-SMPM(F)-300MM	Cable Assembly, SMPM Straight Female to SMPM Straight Female, mBend Cable
VN-NMD18F-24F-26	Cable Assembly, NMD1.85mm Female to 2.4mm Female, VN-24 (VNA Test Cable), 26 Inches
VN-NMD18F-24F-39	Cable Assembly, NMD1.85mm Female to 2.4mm Female, VN-24 (VNA Test Cable), 39 Inches
VN-NMD18F-24M-26	Cable Assembly, NMD1.85mm Female to 2.4mm Male, VN-24 (VNA Test Cable), 26 Inches
VN-NMD18F-24M-39	Cable Assembly, NMD1.85mm Female to 2.4mm Male, VN-24 (VNA Test Cable), 39 Inches
VN-NMD24F-24F-26	Cable Assembly, NMD2.4mm Female to 2.4mm Female, VN-24 (VNA Test Cable), 26 Inches
VN-NMD24F-24F-39	Cable Assembly, NMD2.4mm Female to 2.4mm Female, VN-24 (VNA Test Cable), 39 Inches
VN-NMD24F-24M-26	Cable Assembly, NMD2.4mm Female to 2.4mm Male, VN-24 (VNA Test Cable), 26 Inches
VN-NMD24F-24M-39	Cable Assembly, NMD2.4mm Female to 2.4mm Male, VN-24 (VNA Test Cable), 39 Inches

TERMINATIONS

Product Name	Description
ANO 722-103	Coaxial Termination 2.4mm Male, 1.0 Watts, DC~50GHz
ANO 722-105	Coaxial Termination With Chain, 2.4mm Male, 1.0 Watts, DC-50GHz
ANO 722-109	Coaxial Termination, 2.4mm Male, 30 Watts, DC-50 GHz
ANO 722-111	Coaxial Termination, 2.4mm Male, 2 Watts, DC-50 GHz
ANO 722-204	Coaxial Termination 2.4mm Female, 1.0 Watts, DC~50GHz
ANO 722A-1.20	Precision Standard Mismatches Coaxial Termination, 2.4mm Male, 2 Watts, DC-50GHz, Nominal VSWR 1.20
ANO 722A-1.50	Precision Standard Mismatches Coaxial Termination, 2.4mm Male, 2 Watts, DC-50GHz, Nominal VSWR 1.50
ANO 722A-2.00	Precision Standard Mismatches Coaxial Termination, 2.4mm Male, 2 Watts, DC-50GHz, Nominal VSWR 2.00

50 GHz Products



ANO 722B-1.20	Precision Standard Mismatches Coaxial Termination, 2.4mm Female, 2 Watts, DC-50GHz, Nominal VSWR 1.20
ANO 722B-1.50	Precision Standard Mismatches Coaxial Termination, 2.4mm Female, 2 Watts, DC-50GHz, Nominal VSWR 1.50
ANO 722B-2.00	Precision Standard Mismatches Coaxial Termination, 2.4mm Female, 2 Watts, DC-50GHz, Nominal VSWR 2.00

ATTENUATORS

Product Name	Description
ANO 22-0203-XX	Attenuator, 2.4mm Male To 2.4mm Female, 2w, DC-50GHz
ANO 22-0205-XX	Attenuator, 2.4mm Male to 2.4mm Female, 2W, DC-50GHz
ANO 22-0501-XX	Attenuator, 2.4mm Male to 2.4mm Female, 5 Watts, DC-50 GHz
ANO 22-1001-XX	Attenuator, 2.4mm Male to 2.4mm Female, 10 Watts, DC-50 GHz
ANO 22-1501-XX	Attenuator, 2.4mm Male to 2.4mm Female, 15 Watts, DC-50 GHz

DC BLOCKS

Product Name	Description
D22-A1	Inner DC Block From 30 MHz TO 50 GHz With 2.4mm Connector

TOOLS

Product Name	Description
ANO TW-001	Torque Wrench for SMA/3.5 mm/2.92 mm/2.4 mm/1.85 mm Type Connectors, Preset Torque= 8 ± 0.32 in.lbs, Hex Size =5/16 in.
ANO TW-002	Torque Wrench for SMA/3.5 mm/2.92 mm/2.4 mm/1.85mm Type Connectors, Preset Torque= 12 ± 0.48 in.lbs, Hex Size =5/16 in.
ANO TWSD-003	Torque Wrench in Screwdriver Type for SMA/3.5 mm/2.92 mm/2.4 mm/1.85 mm Type Connectors Preset Torque= 0.9 ± 0.04 Nm [8 ± 0.32 in.lbs]; Hex Size 8.0 mm [5/16 in.]
T21003	SMA, 3.5mm 2.92mm, 2.4mm, 1.85mm Connector-Finger Thumb Wrench Blue

ACCESSORIES

Product Name	Description
ANO 2211-6055	Cap Male, With Chain for 2.4mm and 1.85mm