

## CONNECTORS

Product Name	Description
<a href="#">ANO 4111-2021</a>	NanoRF Socket Contact Assembly Solder for .047 Cable
<a href="#">ANO 2011-2001</a>	0.9mm Straight Male Solder for .047 Cable
<a href="#">ANO 2012-3002</a>	0.9mm Female, 2 Hole Flange Mount, .438 Long Rear Socket to Accept $\varnothing$ 0.30 [.012 Dia] Pin
<a href="#">ANO 6211-2003</a>	1.85MM Straight Male Solder For CXN3506 Cable, Captivated Contact
<a href="#">ANO 6211-2025</a>	1.85mm Straight Male Solder for 047SC-2901 Cable
<a href="#">ANO 6211-2031</a>	1.85mm Straight Male Solder For UT-085/UT-085C-Form Cable Captivated Contact
<a href="#">ANO 6211-2038</a>	1.85mm Straight Male Solder For UT-085/UT-085C-Form Cable
<a href="#">ANO 6211-3010-1</a>	1.85mm Straight Male 2 Hole .551" Flange Mount, Accept .009 Pin Dia, Field Replaceable
<a href="#">ANO 6211-3010-2</a>	1.85mm Straight Male 2 Hole .551" Flange Mount, Accept .012 Pin Dia, Field Replaceable
<a href="#">ANO 6211-3011-1</a>	1.85mm Straight Male 2 Hole .622" Flange Mount, Accept .009" Pin Dia, Field Replaceable
<a href="#">ANO 6211-3011-2</a>	1.85mm Straight Male 2 Hole .622" Flange Mount, Accept .012" Pin Dia, Field Replaceable
<a href="#">ANO 6211-3012-1</a>	1.85mm Straight Male 4 Hole .500" SQ. Flange Mount, Accept .009" Pin Dia.,Field Replaceable
<a href="#">ANO 6211-3012-2</a>	1.85mm Straight Male 4 Hole .500" SQ. Flange Mount, Accept .012" Pin Dia.,Field Replaceable
<a href="#">ANO 6211-3044-1</a>	1.85mm Straight Male 4 Hole .375" SQ Flange Mount, Accept .009 Dia. Pin, Field Replaceable
<a href="#">ANO 6211-3044-2</a>	1.85mm Straight Male 4 Hole .375" SQ Flange Mount, Accept .012 Dia. Pin, Field Replaceable
<a href="#">ANO 6211-3063</a>	1.85mm Male Vertical Launch Stripline, 2 Hole Flange, Compression Mount
<a href="#">ANO 6212-2004</a>	1.85mm Straight Female Solder For Cxn3506 Cable, Captivated Contact
<a href="#">ANO 6212-2026</a>	1.85mm Straight Female Solder For 047SC-2901 Cable
<a href="#">ANO 6212-2030</a>	1.85mm Straight Female Solder for PLEX102P Cable, Captivated Contact
<a href="#">ANO 6212-3037</a>	1.85mm Straight Female, 4 Hole .500 SQ. Flange, Solder For .047 S/R Cable
<a href="#">ANO 6212-2039</a>	1.85mm Straight Female Solder for UT-085/UT-085C-FORM Cable
<a href="#">ANO 6212-2048</a>	1.85mm Straight Bulkhead Waterproof Female Solder for .086 Cable, Captivated Contact
<a href="#">ANO 6212-2052</a>	1.85mm Straight Female Solder for .034 Cable, Solder Direct
<a href="#">ANO 6212-3005</a>	1.85mm Straight Female, 2 Hole .625" SQ. Flange, Solder For .047 S/R Cable
<a href="#">ANO 6212-3013-1</a>	1.85mm Straight Female, 4 Hole .500" SQ. Flange, Accept .009" Pin Dia., Field Replaceable
<a href="#">ANO 6212-3013-2</a>	1.85mm Straight Female, 4 Hole .500" SQ. Flange, Accept .012" Pin Dia., Field Replaceable
<a href="#">ANO 6212-3014-1</a>	1.85mm Straight Female, 2 Hole .622" Long Flange, Accept .009" Pin Dia., Field Replaceable

# 67 GHz Products



<a href="#">ANO 6212-3014-2</a>	1.85mm Straight Female, 2 Hole .622" Long Flange, Accept .012" Pin Dia., Field Replaceable
<a href="#">ANO 6212-3015-1</a>	1.85mm Straight Female, 2 Hole .551" Long Flange, Accept .009" Pin Dia., Field Replaceable
<a href="#">ANO 6212-3015-2</a>	1.85mm Straight Female, 2 Hole .551" Long Flange, Accept .012" Pin Dia., Field Replaceable
<a href="#">ANO 6212-3020-1</a>	1.85mm Straight Female, 2 Hole .500" Long Flange, Accept .009" Pin Dia., Field Replaceable
<a href="#">ANO 6212-3020-2</a>	1.85mm Straight Female, 2 Hole .500" Long Flange, Accept .012" Pin Dia., Field Replaceable
<a href="#">ANO 6212-3035-1</a>	1.85mm Straight Female, 4 Hole .374 SQ. Flange, Accept .009 Dia. Pin, Field Replaceable
<a href="#">ANO 6212-3035-2</a>	1.85mm Straight Female, 4 Hole .374 SQ. Flange, Accept .012 Dia. Pin, Field Replaceable
<a href="#">ANO 6212-3037</a>	1.85mm Straight Female, 4 Hole .500 SQ. Flange, Solder For .047 S/R Cable
<a href="#">ANO 6212-3040</a>	1.85mm Female Vertical Launch, 2 Hole Flange, Compression Mount
<a href="#">ANO 6212-3041</a>	1.85mm Female Vertical Launch, 2 Hole Flange, Compression Mount
<a href="#">ANO 6212-3049</a>	1.85mm Straight Female, 4 Hole .500 SQ. Flange, Solder For .047 S/R Cable
<a href="#">ANO 6212-3051</a>	1.85mm Female 2 Hole Flange, Vertical Launch
<a href="#">ANO 6212-3068</a>	1.85mm Female Vertical Launch Stripline, 4 Hole Flange, Compression Mount
<a href="#">ANO 6212-5054</a>	1.85mm Female Receptacle, Thread Mount Field Replaceable
<a href="#">ANO 621-A1-H</a>	1.85mm Male End Launch Connector Standard Profile, Launch Pin $\varnothing$ 0.18 [.007]
<a href="#">ANO 621-A1-L</a>	1.85mm Male End Launch Connector Low Profile, Launch Pin $\varnothing$ 0.18 [.007]
<a href="#">ANO 621-A2-H</a>	1.85mm Male End Launch Connector Standard Profile, Launch Pin $\varnothing$ 0.13 [.005]
<a href="#">ANO 621-A2-L</a>	1.85mm Male End Launch Connector Low Profile, Launch Pin $\varnothing$ 0.13 [.005]
<a href="#">ANO 622-A1-H</a>	1.85mm Female End Launch Connector, Launch Pin $\varnothing$ 0.18 [.007]
<a href="#">ANO 622-A1-L</a>	1.85mm Female End Launch Connector Low Profile, Launch Pin $\varnothing$ 0.18 [.007]
<a href="#">ANO 622-A2-H</a>	1.85mm Female End Launch Connector, Launch Pin $\varnothing$ 0.13 [.005]
<a href="#">ANO 622-A2-L</a>	1.85mm Female End Launch Connector Low Profile, Launch Pin $\varnothing$ 0.13 [.005]
<a href="#">ANO 622-C1</a>	1.85mm Female End Launch Connector Super Small End Launch-Wide
<a href="#">ANO 6911-2004</a>	NMD1.85mm Straight Male Solder For CXN3506 Cable, Captivated Contact
<a href="#">ANO 6912-2002</a>	NMD1.85mm Straight Female Solder For CXN3506 Cable, Captivated Contact
<a href="#">ANO 7511-2002</a>	MMCX65(MMPX) Straight Angle Male Solder for RG405/.086 Cable
<a href="#">ANO 7511-2003</a>	MMCX65(MMPX) Straight Male Solder for MB103 Cable
<a href="#">ANO 7521-2001</a>	MMCX65(MMPX) Right Angle Male Solder for RG405/.086 Cable
<a href="#">ANO-7811-2005</a>	SMPS Male Solder for .047 Cable, Blind-mate for M38999 Size 16 Cavity

# 67 GHz Products



<a href="#">ANO-7811-2008</a>	SMPS Male Solder for .047 Cable, Blind-mate for 2M805 (MICRO 38999) Receptacle Size 16
<a href="#">ANO-7811-2010</a>	SMPS Male Solder for .086 Cable, Blind-mate for 2M805 (MICRO 38999) Receptacle Size 16
<a href="#">ANO 7811-5002-1</a>	SMPS Straight Male Full Detent 4-Port Edge Launch
<a href="#">ANO 7811-5002-2</a>	SMPS Straight Male Smooth Bore 4-Port Edge Launch
<a href="#">ANO 7811-5012</a>	SMPS (FD) Straight Edge Mount
<a href="#">ANO 7811-5013</a>	SMPS(G3PO) FD Straight Male 4-Port Edge Launch
<a href="#">ANO 7812-2001</a>	SMPS Straight Female Solder for .047 Cable
<a href="#">ANO 7812-2004</a>	SMPS Female Solder for .047 Cable, Blind-Mate for M38999 Size 16 Cavity
<a href="#">ANO 7812-2011</a>	SMPS Female Solder for .086 Cable, Blind-mate for 2M805 (MICRO 38999) Plug Size 16
<a href="#">ANO 9411-1024-1</a>	SMPM Male Full Detent Snap-in Bulkhead Mount for .047 Cable
<a href="#">ANO 9411-1024-2</a>	SMPM Male Smooth Bore Snap-in Bulkhead Mount for .047 Cable
<a href="#">ANO 9411-2023-1</a>	SMPM Straight Male Solder For .086 Cable, Full Detent
<a href="#">ANO 9411-2023-2</a>	SMPM Straight Male Solder For .086 Cable, Smooth Bore
<a href="#">ANO 9411-2034-1</a>	SMPM Straight Male Bulkhead Solder for .086 Cable, Full Detent
<a href="#">ANO 9411-2034-2</a>	SMPM Straight Male Bulkhead Solder for .086 Cable, Smooth Bore
<a href="#">ANO 9411-2037</a>	SMPM Male Smooth Bore Interface FIT M38999 Size 12 Insert Solder for .086 Cable
<a href="#">ANO 9411-2047</a>	SMPM Straight Male Full Detent 2 Hole Flange Mount Shroud, .350" Hole Spacing
<a href="#">ANO 9411-2049-1</a>	SMPM Straight Full Detent Male Bulkhead Solder for .047 Cable
<a href="#">ANO 9411-2049-2</a>	SMPM Straight Smooth Bore Male Bulkhead Solder for .047 Cable
<a href="#">ANO 9411-4001-1</a>	SMPM Straight Male for PCB Mount, Full Detent
<a href="#">ANO 9411-4001-2</a>	SMPM Straight Male for PCB Mount, Smooth Bore
<a href="#">ANO 9411-4053-1</a>	SMPM Straight Plug SMT, Full Detent
<a href="#">ANO 9411-4053-2</a>	SMPM Straight Plug SMT, Smooth Bore
<a href="#">ANO 9411-5009</a>	SMPM Straight Male Panel Mount Thread-In With $\varnothing$ .024 Contact
<a href="#">ANO 9411-5010-1</a>	SMPM Straight Male Full Detent Solder-In Hermetic Shroud With $\varnothing$ .012 Contact, .070 Length
<a href="#">ANO 9411-5010-2</a>	SMPM Straight Male Smooth Bore Solder-In Hermetic Shroud With $\varnothing$ .012 Contact, .070 Length
<a href="#">ANO 9411-5016-1</a>	SMPM-T Straight Male Full Detent, Thread-In With $\varnothing$ .012 Contact
<a href="#">ANO 9411-5016-2</a>	SMPM-T Straight Male Smooth Bore, Thread-In With $\varnothing$ .012 Contact
<a href="#">ANO 9411-5041-1</a>	SMPM-T Straight Male For PCB Mount, Full Detent

<a href="#">ANO 9411-5041-2</a>	SMPM-T Straight Male For PCB Mount, Smooth Bore
<a href="#">ANO 9411-5054-1</a>	SMPM-T Straight Full Detent Male, Launcher, (Board Edge Mount)
<a href="#">ANO 9411-5054-2</a>	SMPM-T Straight Smooth Bore Male, Launcher, (Board Edge Mount)
<a href="#">ANO 9411-5074-1</a>	SMPM Straight Male Full Detent, 4-Port Edge Launch
<a href="#">ANO 9411-5074-2</a>	SMPM Straight Male Smooth Bore, 4-Port Edge Launch
<a href="#">ANO 9411-5077</a>	SMPM Straight Male Full Detent 8 Port Edge Mount
<a href="#">ANO 9411-5089-1</a>	SMPM-T Male Smooth Bore Edge Launch Connector, PCB Thickness= 0.81[.032]-3.12[.123]
<a href="#">ANO 9411-5089-2</a>	SMPM-T Male Smooth Bore Edge Launch Connector, PCB Thickness= 2.39[.094]-4.70[.185]
<a href="#">ANO 9411-6040-1</a>	SMPM-T Straight Male Full Detent, Solder-In Hermetic Shroud With $\varnothing$ .012 Contact, Contact Length=1.52[.06]
<a href="#">ANO 9411-6040-2</a>	SMPM-T Straight Male Full Detent, Solder-In Hermetic Shroud With $\varnothing$ .012 Contact, Contact Length=2.28[.09]
<a href="#">ANO 9411-6040-3</a>	SMPM-T Straight Male Smooth Bore, Solder-In Hermetic Shroud With $\varnothing$ .012 Contact, Contact Length=1.52[.06]
<a href="#">ANO 9411-6040-4</a>	SMPM-T Straight Male Smooth Bore, Solder-In Hermetic Shroud With $\varnothing$ .012 Contact, Contact Length=2.28[.09]
<a href="#">ANO 9411-6051</a>	SMPM Straight Male Screw Type Smooth Bore
<a href="#">ANO 9412-2004</a>	SMPM Straight Female Solder For .047 Cable
<a href="#">ANO 9412-2021</a>	SMPM-QT(SMPM Quaterturn) Straight Female Nut for .086 Cable
<a href="#">ANO 9412-2022</a>	SMPM-T Straight Female Solder For .047 Cable
<a href="#">ANO 9412-2032</a>	SMPM-T Straight Female Solder For .086 Cable
<a href="#">ANO 9412-2043</a>	SMPM Female T-FLEX 405 Cable Fit M38999 Size 12 Insert
<a href="#">ANO 9412-5046</a>	SMPM Straight Female, Panel Mount Thread-in for .020 Dia. Post
<a href="#">ANO-9412-2084</a>	SMPM Straight Female Solder for MB103 Cable
<a href="#">ANO-9412-2085</a>	SMPM Straight Female Solder for .086 Cable
<a href="#">ANO 9421-5042-1</a>	SMPM-T Right Angle Male For PCB Mount, Full Detent
<a href="#">ANO 9421-5042-2</a>	SMPM-T Right Angle Male For PCB Mount, Smooth Bore
<a href="#">ANO 9422-2007</a>	SMPM R/A Female Solder for .047 S/R Cable
<a href="#">ANO 9422-2014</a>	SMPM R/A Female Solder For .047 S/R Cable

## ADAPTERS

Product Name	Description
<a href="#">ANO 621-941-1524-1</a>	Adapter, 1.85mm Male To SMPM-T Male, Full Detent
<a href="#">ANO 621-941-1524-2</a>	Adapter, 1.85mm Male To SMPM-T Male, Smooth Bore

# 67 GHz Products



<a href="#">ANO 622-941-1525-1</a>	Adapter, 1.85mm Female To SMPM-T Male Full Detent
<a href="#">ANO 622-941-1525-2</a>	Adapter, 1.85mm Female To SMPM-T Male Smooth Bore
<a href="#">ANO 941-941-1456-1</a>	Adapter, SMPM Male to SMPM Male, Full Detent
<a href="#">ANO 941-941-1456-2</a>	Adapter, SMPM Male to SMPM Male, Smooth Bore
<a href="#">ANO 941-941-1512</a>	Adapter, SMPM Male to SMPM Male
<a href="#">ANO 941-941-1542-1</a>	Adapter, SMPM-T Male to SMPM-T Male, Full Detent
<a href="#">ANO 941-941-1542-2</a>	Adapter, SMPM-T Male to SMPM-T Male, Smooth Bore
<a href="#">ANO 941-941-1546</a>	Adapter, SMPM Male(FD) to SMPM Male(FD), Hermetic Seal
<a href="#">ANO 942-942-1381</a>	Adapter, SMPM Female To SMPM Female, L=6.73 [.265]
<a href="#">ANO 942-942-1415</a>	Adapter, SMPM Spring Loaded Female To SMPM Female
<a href="#">ANO 942-942-1526</a>	Adapter, SMPM Female To SMPM Female, L=5.36 [.211]
<a href="#">ANO 942-942-1527</a>	Adapter, SMPM Female To SMPM Female, L=12.7 [.500]
<a href="#">ANO-942-942-1681</a>	Adapter, SMPM Female To SMPM Female, L=6.1 [.240]
<a href="#">PA6220C</a>	Precision Adapter 1.85mm Female To 0.9mm Female
<a href="#">PA6220D</a>	Precision Adapter 1.85mm Female To 0.9mm Male
<a href="#">PA6262A</a>	Precision Adapter, 1.85mm Male To 1.85mm Male
<a href="#">PA6262B</a>	Precision Adapter 1.85mm Male To 1.85mm Female
<a href="#">PA6262C</a>	Precision Adapter 1.85mm Female To 1.85mm Female
<a href="#">PA6262CA</a>	Precision Adapter, 1.85mm Bulkhead Female to 1.85mm Female
<a href="#">PA6262E</a>	Precision Adapter, 1.85mm Bulkhead Female to 1.85mm Female
<a href="#">PA6262EA</a>	Precision Adapter, 1.85mm Bulkhead Female to 1.85mm Female
<a href="#">PA6262F</a>	Precision Adapter, 1.85 Female to 1.85 Female 4 Hole Flange
<a href="#">PA6262FA</a>	Precision Adapter, 1.85mm Female to 1.85mm Female, 2 Hole Flange
<a href="#">PA6262FB</a>	Precision Adapter, 1.85mm Female to 1.85mm Female, 4 Hole Flange
<a href="#">PA6262J</a>	Precision Adapter, Right Angle 1.85mm Male To 1.85mm Male
<a href="#">PA6262K</a>	Precision Adapter, Right Angle 1.85mm Male To 1.85mm Female
<a href="#">PA6262L</a>	Precision Adapter, Right Angle 1.85mm Female To 1.85mm Female
<a href="#">PA6262S</a>	Precision Adapter, 1.85mm Bulkhead Male to 1.85mm Female
<a href="#">PA6276A</a>	Precision Adapter, 1.0mm Male to 1.85mm Male

<a href="#">PA6276B</a>	Precision Adapter, 1.0mm Male to 1.85mm Female
<a href="#">PA6276C</a>	Precision Adapter, 1.0mm Female to 1.85mm Female
<a href="#">PA6276D</a>	Precision Adapter, 1.0mm Female to 1.85mm Male
<a href="#">PA6278A</a>	Precision Adapter, SMPS Male Full Detent to 1.85mm Male
<a href="#">PA6278B</a>	Precision Adapter, SMPS Female to 1.85mm Male
<a href="#">PA6278C</a>	Precision Adapter, SMPS Female to 1.85mm Female
<a href="#">PA6278D</a>	Precision Adapter, SMPS Male Full Detent To 1.85mm Female
<a href="#">PA6294A</a>	Precision Adapter, 1.85mm Male To SMPM Male
<a href="#">PA6294B</a>	Adapter, 1.85mm Male to SMPM Female
<a href="#">PA6294C</a>	Adapter, 1.85mm Female to SMPM Female
<a href="#">PA6294D</a>	Precision Adapter, 1.85mm Female To SMPM Male
<a href="#">PA6962B</a>	Precision Adapter, NMD1.85mm Male to 1.85mm Female
<a href="#">PA6962C</a>	Precision Adapter, NMD1.85mm Female to 1.85mm Female
<a href="#">PA6962CA</a>	Precision Adapter, NMD1.85mm Female To 1.85mm Female
<a href="#">PA6962D</a>	Precision Adapter, NMD1.85mm Female to 1.85mm Male
<a href="#">PA6962S</a>	Precision Adapter, NMD1.85mm Male To 1.85mm Female, Panel Mount
<a href="#">PA6969B</a>	Precision Adapter, NMD1.85mm Female to NMD1.85mm Male
<a href="#">PA7678D</a>	Precision Adapter, SMPS Male Full Detent to 1.0mm Female
<a href="#">PA8062A</a>	Precision Adapter, 1.35mm Male To 1.85mm Male
<a href="#">PA8062B</a>	Precision Adapter, 1.35mm Female to 1.85mm Male
<a href="#">PA8062C</a>	Precision Adapter, 1.35mm Female To 1.85mm Female
<a href="#">PA8062D</a>	Precision Adapter, 1.35mm Male to 1.85mm Female

## CABLES

Product Name	Description
<a href="#">SR086LL</a>	Low Loss Semi-Rigid Series Cable, 50 Ohm, With Copper Tube
<a href="#">SR086AP-LL</a>	Semi-Rigid Series Cable, SR086AP-LL with Albaloy Plated Copper Tube
<a href="#">HTC-047P</a>	Flexible Coaxial Cable, HTC-047P with Blue FEP Jacket
<a href="#">MB067</a>	MB Series Cable, MB067 With Blue FEP Jacket
<a href="#">MB098</a>	MB Series Cable, MB098 With Blue FEP Jacket

<a href="#">PLEX090</a>	PLEX Series Cable, PLEX090 With FEP Jacket
<a href="#">PLEX090-lite</a>	PLEX-lite Series Cable, PLEX090-lite with eTFE Jacket
<a href="#">PLEX090DBK</a>	PLEX Series Cable, PLEX090DBK With Black FEP Jacket
<a href="#">PLEX102P</a>	PLEX Series Cable, PLEX102P With FEP Jacket
<a href="#">PLEX102S</a>	PLEX Series Cable, PLEX102S With Blue PUR Jacket
<a href="#">SR070LLTP</a>	Low Loss Semi-Rigid Series Cable, 50 Ohm, with Tin Plated Copper Tube
<a href="#">SUPO-057P</a>	SUPO Series Cable, SUPO-057P with FEP Jacket
<a href="#">SUPO-090</a>	SUPO Series Cable, SUPO-090 with FEP Jacket

## CABLE ASSEMBLIES

Product Name	Description
<a href="#">047X-18F-18F-15</a>	047X Coaxial Cable 1.85mm Female to 1.85 Female
<a href="#">AF047-18M-18F-3</a>	Cable Assembly, 1.85mm Straight Male to 1.85mm Straight Female, AFLEX047 Cable, 3 Inches
<a href="#">AF047-18M-18M-14</a>	Cable Assembly, 1.85mm Male to 1.85mm Male, AFLEX047 Cable
<a href="#">AF047-1F-SMPM(F)-3</a>	Cable Assembly, 1mm Straight Female to SMPM Straight Female, AFLEX047 Cable, 3 Inches
<a href="#">AF047-1M-18M-6.8CM</a>	Cable Assembly, 1.0mm Straight Male to 1.85mm Straight Male, AFLEX047 Cable, 6.8cm
<a href="#">AF047-18M-SMPS(F)-10</a>	Cable Assembly, 1.85mm Straight Male to SMPS Female, Blind-mate for 2M805(MICRO 38999) Plug Size 16, AFLEX047 Cable, 10 inches
<a href="#">AF047-SMPS(F)-SMPS(F)</a>	Cable Assembly, SMPS Straight Female to SMPS Straight Female, AFLEX047 Cable, 200mm
<a href="#">AF047-SMPS(F)-SMPS(F)</a>	Cable Assembly, SMPS Straight Female to SMPS Straight Female, AFLEX047 Cable
<a href="#">AF086-SMPM(F)-18M-20</a>	Cable Assembly, SMPM Straight Female to 1.85mm Straight Male, AFLEX086 Cable, 200mm
<a href="#">SR047LL-18M-18M-18</a>	Cable Assembly, 1.85mm Straight Male to 1.85mm Straight Male, SR047LL Cable, 18 Inches
<a href="#">SR047-SMPSF-185M-2</a>	Cable Assembly, SMPS Straight Female to 1.85mm Straight Male, ANO SR047 Cable, 2 Inches
<a href="#">SR086LL-18M-18M-18-P</a>	Cable Assembly, 1.85mm Straight Male to 1.85mm Straight Male, SR086LL Cable, 18 Inches
<a href="#">P102P-18M-18M-2M</a>	Cable Assembly, 1.85mm Straight Male to 1.85mm Straight Male, PLEX102P Cable, 2 Meters
<a href="#">PT-18F-18F-26</a>	Cable Assembly, 1.85mm Female to 1.85mm Female, PT-18 (PT Series Precision Test Cables), 26 Inches
<a href="#">PT-18F-18F-39</a>	Cable Assembly, 1.85mm Female to 1.85mm Female, PT-18 (PT Series Precision Test Cables), 39 Inches
<a href="#">PT-18M-18F-26</a>	Cable Assembly, 1.85mm Male to 1.85mm Female, PT-18 (PT Series Precision Test Cables), 26 Inches
<a href="#">PT-18M-18F-39</a>	Cable Assembly, 1.85mm Male to 1.85mm Female, PT-18 (PT Series Precision Test Cables), 39 Inches
<a href="#">PT-18M-18M-26</a>	Cable Assembly, 1.85mm Male to 1.85mm Male, PT-18 (PT Series Precision Test Cables), 26 Inches
<a href="#">PT-18M-18M-39</a>	Cable Assembly, 1.85mm Male to 1.85mm Male, PT-18 (PT Series Precision Test Cables), 39 Inches

<a href="#">VN-NMD18F-18F-26</a>	Cable Assembly, NMD1.85mm Female to 1.85mm Female, VN-18 (VNA Test Cable), 26 Inches
<a href="#">VN-NMD18F-18F-39</a>	Cable Assembly, NMD1.85mm Female to 1.85mm Female, VN-18 (VNA Test Cable), 39 Inches
<a href="#">VN-NMD18F-18M-26</a>	Cable Assembly, NMD1.85mm Female to 1.85mm Male, VN-18 (VNA Test Cable), 26 Inches
<a href="#">VN-NMD18F-18M-39</a>	Cable Assembly, NMD1.85mm Female to 1.85mm Male, VN-18 (VNA Test Cable), 39 Inches
<a href="#">WP-18(90°)M-18F-1.2M</a>	Wafer Probing Cable, 1.85mm Female to 1.85mm Male (90 Degree Bended), PLEX102P Cable, 1.2 Meters

## TERMINATIONS

Product Name	Description
<a href="#">ANO 762-101</a>	Coaxial Termination, 1Watt, 1.85mm Male DC-67GHz, VSWR 1.35 Max.
<a href="#">ANO 762-108</a>	Coaxial Termination, 1.85mm Male, 2 Watts, DC-67GHz, VSWR 1.30 Max.
<a href="#">ANO 762-111</a>	Coaxial Termination, 1.85mm Male, 2 Watts, DC-67 GHz, VSWR: 1.15 MAX.
<a href="#">ANO 762-202</a>	Coaxial Termination, 1 Watt, 1.85mm Female DC-67GHz, VSWR 1.35 Max.
<a href="#">ANO 762-212</a>	Coaxial Termination, 1.85mm Female, 2 Watts, DC-67 GHz, VSWR: 1.15 MAX.

## ATTENUATORS

Product Name	Description
<a href="#">ANO 62-0201-XX</a>	Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
<a href="#">ANO 62-0202-XX</a>	Attenuator, 1.85mm Female to 1.85mm Female, 2 W, DC-67 GHz
<a href="#">ANO 62-0203-80</a>	80 dB Attenuator, 1.85mm Male to 1.85mm Female, 2 W, DC-67 GHz
<a href="#">ANO 62-0501-XX</a>	Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz

## DC BLOCKS

Product Name	Description
<a href="#">D62-A1</a>	DC Block on Inner Conductor 1.85mm Male to 1.85mm Female Operating From 50 MHz to 67 GHz

## TOOLS

Product Name	Description
<a href="#">ANO TW-001</a>	Torque Wrench for SMA/3.5 mm/2.92 mm/2.4 mm/1.85 mm Type Connectors, Preset Torque=8±0.32 in.lbs, Hex Size =5/16 in.
<a href="#">ANO TW-002</a>	Torque Wrench for SMA/3.5 mm/2.92 mm/2.4 mm/1.85mm Type Connectors, Preset Torque= 12±0.48 in.lbs, Hex Size =5/16 in.
<a href="#">ANO TWSD-001</a>	Torque Wrench in Screwdriver Type, for SMA /3.5mm /2.92mm /2.4mm /1.85mm Type Connectors, Preset Torque= 0.9±0.04 NM [8±0.32 IN.LBS], Hex Size 7.94 MM [5/16 IN.]
<a href="#">T21003</a>	SMA, 3.5mm 2.92mm, 2.4mm, 1.85mm Connector-Finger Thumb Wrench Blue