

4

3

2

1

MATERIAL & FINISH:

- 1 BODY: BRASS, GOLD PLATED
- 2 CENTER CONTACT: PHOSPHOR BRONZE, GOLD PLATED
- 3 INSULATOR: PTFE
- 4 SPRING LATCH: BERYLLIUM COPPER ALLOY, GOLD PLATED
- 5 INSULATOR: PTFE
- 6 CAP: BRASS, GOLD PLATED
- 7 CRIMP FERRULE: COPPER, NICKEL PLATED

ELECTRICAL DATA:

- 1 IMPEDANCE: 50 Ω
- 2 FREQUENCY RANGE: DC~6 GHz

ENVIRONMENTAL DATA:

- 1 TEMPERATURE RANGE: -55°C~+125°C
- 2 2011/65/EU (RoHS): COMPLIANT

REVISIONS

REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	04/11/17	J. QU

CABLE STRIPPING DIMENSIONS

HEX. CRIMP TOOL

CRIMP WIDTH: 9.0 [.354]

DRAWN	X. B. YANG	DATE	04/11/17
CHECKED	W. YANG	DATE	04/11/17
APPROVED	J. QU	DATE	04/11/17
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN [] ARE IN INCHES FOR CUSTOMER REFERENCE ONLY UNLESS OTHERWISE SPECIFIED TOLERANCE ARE:		THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ANOISON ELECTRONICS LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION COPYRIGHT © 2017 ANOISON ELECTRONICS LTD	
.XX	±0.13 [.005"]		
.X	±0.20 [.008"]		
X	±0.50 [.019"]		
.X°	±1°		
X°	±2°		

TITLE
MMCX RIGHT ANGLE PLUG CRIMP FOR
RG316D (DOUBLE BRAIDED) CABLE

VIEW

PART NO.

ANO 1121-2035

SIZE
A3SCALE
8:1SHEET
1/1REV.
A

4

3

2

1