

1.0 MATERIAL & FINISH:

- 1.1 BODY: STAINLESS STEEL, PASSIVATED
- 1.2 CENTER CONTACT: BERYLLIUM COPPER ALLOY, GOLD PLATED
- 1.3 SOLDER FERRULE: BRASS, GOLD PLATED
- 1.4 COUPLING NUT: STAINLESS STEEL, PASSIVATED
- 1.5 INSULATOR: PTFE & PEI

2.0 ELECTRICAL DATA:

- 2.1 IMPEDANCE: 50 Ω
- 2.2 FREQUENCY RANGE: DC~26.5GHZ
- 2.3 VSWR: 1.25 TYP.



3.0 ENVIRONMENTAL DATA:

- 3.1 TEMPERATURE RANGE: -55°C~+125°C
- 3.2 2011/65/EU (RoHS): COMPLIANT

4.0 MECHANICAL DATA:

- 4.1 MECHANICAL DURABILITY: 500 CYCLES MIN.
- 4.2 CENTER CONTACT: CAPTIVATED
- 4.3 OUTER CONTACT: SOLDERED

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	03/04/16	J. QU
B	DRAWING FORMAT CHANGED	08/29/17	J. QU
C	PART NO. ANO 2111-2383-I WAS ANO 2111-2383A	11/27/17	J. QU



CABLE STRIPPING DIMENSIONS

PART NO.	CABLE
ANO 2111-2383	IWI501
ANO 2111-2383-I	PLEXI40

DRAWN	X. B. YANG	DATE	11/27/17
CHECKED	P. CHEN	DATE	11/27/17
APPROVED	J. QU	DATE	11/27/17
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES FOR CUSTOMER REFERENCE ONLY UNLESS OTHERWISE SPECIFIED TOLERANCE ARE:		THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ANOISON ELECTRONICS LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION COPYRIGHT © 2017 ANOISON ELECTRONICS LTD	
.XX	±0.13 [.005"]		
.X	±0.20 [.008"]		
X	±0.50 [.019"]		
.X°	±1°		
X°	±2°		



TITLE
SMA STRAIGHT MALE SOLDER FOR IWI501/PLEXI40 CABLE CAPTIVATED CONTACT

VIEW	PART NO. ANO 2111-2383			
	SIZE A3	SCALE 5:1	SHEET 1/1	REV. C