

4

3

2

1

MATERIAL & FINISH:

- 1 BODY: STAINLESS STEEL, PASSIVATED
- 2 CENTER CONTACT: BERYLLIUM COPPER ALLOY, GOLD PLATED
- 3 INSULATOR: PTFE

ELECTRICAL DATA:

- 1 IMPEDANCE: 50 Ω
- 2 FREQUENCY RANGE: DC~18 GHz
- 3 VSWR: 1.25 MAX.

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	04/05/17	J. QU

ENVIRONMENTAL DATA:

- 1 TEMPERATURE RANGE: -40°C~+85°C
- 2 2011/65/EU (RoHS): COMPLIANT

12.70
[.500]

8.64
[.340]

8.64
[.340]

12.70
[.500]

4- \varnothing 2.60
[.102 DIA.]

9.53
[.375]

5.00
[.197]

18.00
[.709]

1.65
[.065]

1/4-36UNS-2A

EPOXY



\varnothing 4.10
[.161 DIA.]

\varnothing 1.27
[.050 DIA.]

DRAWN	X. B. YANG	DATE	04/05/17
CHECKED	W. YANG	DATE	04/05/17
APPROVED	J. QU	DATE	04/05/17
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES FOR CUSTOMER REFERENCE ONLY UNLESS OTHERWISE SPECIFIED TOLERANCE ARE:		THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ANOISON ELECTRONICS LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION COPYRIGHT © 2017 ANOISON ELECTRONICS LTD	
.XX	±0.13 [0.005"]		
.X	±0.20 [0.008"]		
X	±0.50 [0.019"]		
.X°	±1°		
X°	±2°		

TITLE

SMA STRAIGHT FEMALE, 4 HOLE FLANGE MOUNT POST CONTACT

VIEW	PART NO.		
 	ANO 2112-3444		
SIZE	SCALE	SHEET	REV.
A3	4:1	1/1	A

4

3

2

1