

4

3

2

1

1.0 MATERIAL &amp; FINISH:

1.1 BODY: STAINLESS STEEL, PASSIVATED

1.2 CENTER CONTACT: BERYLLIUM COPPER ALLOY, GOLD PLATED

1.3 SOLDER FERRULE: BRASS, GOLD PLATED

1.4 COUPLING NUT: STAINLESS STEEL, PASSIVATED

1.5 INSULATOR: PEI

3.0 ENVIRONMENTAL DATA:

3.1 TEMPERATURE RANGE: -55°C~+125°C

3.2 2011/65/EU(RoHS) AND 2015/863/(RoHS): COMPLIANT

3.3 1999/45/EC(REACH): COMPLIANT

2.0 ELECTRICAL DATA:

2.1 IMPEDANCE: 50 Ω

2.2 FREQUENCY RANGE: DC~40GHZ

REVISIONS

REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	11/19/18	J. QU

CABLE STRIPPING DIMENSIONS

DRAWN	P. CHEN	DATE	11/19/18	
CHECKED	X. B. YANG	DATE	11/19/18	
APPROVED	J. QU	DATE	11/19/18	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [ ] ARE IN INCHES FOR CUSTOMER REFERENCE ONLY UNLESS OTHERWISE SPECIFIED TOLERANCE ARE: .XX ±0.13 [.005"] .X ±0.20 [.008"] X ±0.50 [.019"] .X° ±1° X° ±2°		THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ANOISON ELECTRONICS LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION COPYRIGHT © 2018 ANOISON ELECTRONICS LTD		TITLE 2.92MM STRAIGHT MALE SOLDER FOR SR141/RG402 CABLE, CAPTIVATED CONTACT
VIEW		PART NO.		SHEET 1/1 REV. A
		ANO 2911-2103		
SIZE	A3	SCALE	5:1	

4

3

2

1