

4

3

2

1

MATERIAL & FINISH:

- 1 BODY: STAINLESS STEEL, GOLD PLATED
- 2 CENTER CONTACT: BERYLLIUM COPPER ALLOY, GOLD PLATED
- 3 INSULATOR: PEI

ELECTRICAL DATA:

- 1 IMPEDANCE: 50 Ω
- 2 FREQUENCY RANGE: DC~40 GHz
- 3 VSWR: 1.20 MAX.

REVISIONS

REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	04/05/17	J. QU

ENVIRONMENTAL DATA:

- 1 TEMPERATURE RANGE: -55°C~+125°C
- 2 2011/65/EU (RoHS): COMPLIANT

4-Ø2.60
[.102 DIA.]

4.80
[.189]

9.02
[.355]

12.70
[.500]

9.53
[.375]

1.65
[.065]

7.62
[.300]

10.00
[.394]

0.05~0.13
[.002~.005]

Ø0.64
[.025 DIA.]

1/4-36UNS-2A

RP

DRAWN	X. B. YANG	DATE	04/05/17
CHECKED	W. YANG	DATE	04/05/17
APPROVED	J. QU	DATE	04/05/17
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN [] ARE IN INCHES FOR CUSTOMER REFERENCE ONLY UNLESS OTHERWISE SPECIFIED TOLERANCE ARE:		THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ANOISON ELECTRONICS LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION COPYRIGHT © 2017 ANOISON ELECTRONICS LTD	
.XX	±0.08 [.003"]		
.X	±0.20 [.008"]		
X	±0.50 [.019"]		
.X°	±1°		
X°	±2°		

TITLE
2.92MM FEMALE, 2 HOLE FLANGE MOUNT
POST CONTACT

VIEW	PART NO. ANO 2912-3083		
	SIZE A3	SCALE 5:1	SHEET 1/1
			REV. A

4

3

2

1