

4

3

2

1

MATERIAL & FINISH:

- 1 BODY: STAINLESS STEEL, PASSIVATED
- 2 CENTER CONTACT: BERYLLIUM COPPER ALLOY, GOLD PLATED
- 3 INSULATOR: PEI & PTFE

ELECTRICAL DATA:

- 1 IMPEDANCE: 50 Ω
- 2 FREQUENCY RANGE: DC~40 GHz
- 3 VSWR: 1.30 MAX.

ENVIRONMENTAL DATA:

- 1 TEMPERATURE RANGE: -55°C~+125°C
- 2 2011/65/EU(RoHS) AND 2015/863/(RoHS): COMPLIANT
- 3 1999/2006/EC(REACH): COMPLIANT

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	07/13/23	J. Q
B	1.4[.055] WAS 4.0[.157]	07/17/23	J. Q

DRAWN	W. Y	DATE	07/17/23	
CHECKED	X. Y	DATE	07/17/23	
APPROVED	J. Q	DATE	07/17/23	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN [] ARE IN INCHES FOR CUSTOMER REFERENCE ONLY UNLESS OTHERWISE SPECIFIED TOLERANCE ARE:		THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ANOISON ELECTRONICS LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION COPYRIGHT © 2023 ANOISON ELECTRONICS LTD		TITLE
XX ±0.13 [0.005"] X ±0.20 [0.008"] X ±0.50 [0.019"] X° ±1° X° ±2°				2.92MM FEMALE, 2 HOLE FLANGE MOUNT, EXTENDED DIELECTRIC, POST CONTACT
				VIEW
				PART NO.
				ANO 2912-3186
				SIZE
				A3
				SCALE
				4:1
				SHEET
				1/1
				REV.
				B

4

3

2

1