

4

3

2

1

MATERIAL &amp; FINISH:

- 1 BODY: BRASS, NICKEL PLATED
- 2 CENTER CONTACT: BERYLLIUM COPPER ALLOY, GOLD PLATED
- 3 OUTER CONTACT: BERYLLIUM COPPER ALLOY, NICKEL PLATED
- 4 INSULATOR: PTFE

ELECTRICAL DATA:

- 1 IMPEDANCE: 50  $\Omega$
- 2 FREQUENCY RANGE: DC~18 GHz
- 3 VSWR: 1.35 MAX.
- 4 INSERTION LOSS: 0.3 dB MAX.

MECHANICAL DATA:

- 1 MATING CYCLE: 500 MIN.

ENVIRONMENTAL DATA:

- 1 TEMPERATURE RANGE: -55°C~+125°C
- 2 2011/65/EU(RoHS) AND 2015/863/(RoHS): COMPLIANT
- 3 1907/2006/EC(REACH): COMPLIANT

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	04/08/25	J. Q.

REF. 30.3  
[1.193]

SW9.0  
[.354 AF.]

TNC FEMALE

7/16-28UNEF-2A

PUSH ON TNC MALE

REF. Ø11.1  
[.437 DIA.]

Ø15  
[.591 DIA.]

REF. 1  
[.039]

DRAWN	Y. H	DATE	04/08/25
CHECKED	W. Y	DATE	04/08/25
APPROVED	J. Q	DATE	04/08/25
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN [ ] ARE IN INCHES FOR CUSTOMER REFERENCE ONLY UNLESS OTHERWISE SPECIFIED TOLERANCE ARE:		THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ANOISON ELECTRONICS LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION COPYRIGHT © 2025 ANOISON ELECTRONICS LTD	
.XX	±0.13 [.005"]		
.X	±0.20 [.008"]		
X	±0.50 [.019"]		
X*	±1°		
X*	±2°		

TITLE	ADAPTER, PUSH ON TNC MALE TO TNC FEMALE		
-------	---	--	--

VIEW	PART NO. ANO 331-332-1705		
	SIZE A3	SCALE 4:1	SHEET 1/1
		REV. A	

4

3

2

1