

4

3

2

1

MATERIAL & FINISH:

1 BODY: BRASS, ALBALOY PLATED
 2 CENTER CONTACT: PHOSPHOR BRONZE, SILVER PLATED
 3 INSULATOR: PTFE
 4 COUPLING NUT: BRASS, ALBALOY PLATED
 5 O-RING: SILICONE RUBBER

ELECTRICAL DATA:

1 IMPEDANCE: 50 Ω
 2 FREQUENCY RANGE: DC~6 GHz
 3 VSWR: ≤1.25 @ DC~3 GHz
 ≤1.35 @ 3~6 GHz

ENVIRONMENTAL DATA:

1 TEMPERATURE RANGE: -55°C~+125°C
 2 2011/65/EU(ROHS) AND 2015/863/(ROHS): COMPLIANT
 3 1999/45/EC(REACH): COMPLIANT
 4 IP RATING(INTERFACE MATED): IP54

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	11/16/15	J. Q
B	TIGHTENING TORQUE CHANGED	02/24/16	J. Q
C	ADD IP RATING(INTERFACE MATED): IP54	02/25/26	J. Q

CABLE STRIPPING DIMENSIONS

DRAWN	Y. H	DATE	02/25/26
CHECKED	P. C	DATE	02/25/26
APPROVED	J. Q	DATE	02/25/26
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN [] ARE IN INCHES FOR CUSTOMER REFERENCE ONLY UNLESS OTHERWISE SPECIFIED TOLERANCE ARE:		THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ANOISON ELECTRONICS LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION COPYRIGHT © 2026 ANOISON ELECTRONICS LTD	
.XX	±0.13 [.005"]		
.X	±0.20 [.008"]		
X	±0.50 [.019"]		
.X°	±1°		
X°	±2°		

TITLE
TNC MALE STRAIGHT CLAMP FOR 1/4" SUPER FLEX CABLE

VIEW	PART NO. ANO 3311-2062			
	SIZE A3	SCALE 2:1	SHEET 1/1	REV. C

4

3

2

1