

4

3

2

1

MATERIAL & FINISH:

- 1 BODY: BRASS, ALBALOY PLATED
- 2 CENTER CONTACT: PHOSPHOR BRONZE, SILVER PLATED
- 3 INSULATOR: PTFE
- 4 COUPLING NUT: BRASS, ALBALOY PLATED
- 5 GASKET: SILICONE RUBBER

ELECTRICAL DATA:

- 1 IMPEDANCE: 50 Ω
- 2 FREQUENCY RANGE: DC~12 GHz
- 3 VSWR : \leq 1.20 AT DC~6 GHz

ENVIRONMENTAL DATA:

- 1 TEMPERATURE RANGE: -55°C ~ +90°C
- 2 2011/65/EU (RoHS): COMPLIANT

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	09/02/16	J. QU
B	MOVE SWI5[.591 AF]	11/01/17	J. QU

REF. 31.00
[1.22]

$\phi 4.00$
[.157 DIA.]

$\phi 5.60$
[.220 DIA.]

$\phi 16.30$
[.642 DIA.]

SW 22
[.866 HEX.]

3.50
[0.53]

$\phi 6.40$
[.252 DIA.]

$\phi 7.40$
[.291 DIA.]

16.00
[0.63]

7.00
[0.28]

5.00
[0.20]

CABLE STRIPPING DIMENSIONS

HEX. 6.40 [.252]
WIDTH: 12.7 [.500]

CRIMP DIE

DRAWN	P. CHEN	DATE	11/01/17	<p>...we create connection for technologies</p>
CHECKED	L. YANG	DATE	11/01/17	
APPROVED	J. QU	DATE	11/01/17	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLINMETERS, DIMENSIONS IN [] ARE IN INCHES FOR CUSTOMER REFERENCE ONLY UNLESS OTHERWISE SPECIFIED TOLERANCE ARE:		THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ANOISON ELECTRONICS LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION COPYRIGHT © 2017 ANOISON ELECTRONICS LTD		TITLE
.XX ± 0.13 [.005"] .X ± 0.20 [.008"] X ± 0.50 [.019"] .X° $\pm 1^\circ$ X° $\pm 2^\circ$				SCREW 4.3-10 STRAIGHT MALE CRIMP FOR LMR240 CABLE, CAPTIVATED CONTACT
				VIEW
				PART NO.
				ANO 4711-2022
		SIZE	SCALE	SHEET
		A3	2:1	1/1
		REV.	B	

4

3

2

1