MATERIAL & FINISH:

1 BODY: BRASS, ALBALOY PLATED
2 CENTER CONTACT: BERYLLIUM COPPER ALLOY, GOLD PLATED
3 INSULATOR: PTFE
4 COUPLING NUT: BRASS, ALBALOY PLATED
5 O-RING: SILICONE RUBBER

ENVIRONMENTAL DATA:

1 TEMPERATURE RANGE: -55℃~+125℃
2 2011/65/EU(RoHS) AND 2015/863/(RoHS): COMPLIANT
3 1907/2006/EC(REACH): COMPLIANT

ELECTRICAL DATA:

1 IMPEDANCE: 50 Ω
2 FREQUENCY RANGE: DC~18 GHz
3 VSWR: 1.35 MAX.
4 AVERAGE POWER: MAXIUM POWER 5 WATTS AVERAGE TO 25°C AMBIENT TEMPERATRUE, DERATED LINEARLY TO 0.5W @ 125°C
5 PEAK POWER: MAXIUM POWER 200 W (5μS PLUSE WIDTH WITH THE MAXIMUM 1% DUTY CYCLE)
6 ATTENUATOR ACCURACY: SEE TABLE

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	11/09/22	J. Q



PART NO.	ATTENUATION VALUES & ACCURACY					
	1 dB~10dB	20 dB	30 dB	40 dB	50 dB	60 dB
ANO 51-0506-XX	±0.7 dB	±0.8 dB	±1.0 dB	±1.2 dB	±1.3 dB	±1.3 dB

DRAWN	X. Y	DATE 11/09/22
CHECKED	W. Y	DATE 11/09/22
APPROVED	J. Q	DATE 11/09/22

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN [ ] ARE IN INCHES FOR CUSTOMER REFERENCE ONLY UNLESS OTHERWISE SPECIFIED TOLERANCE ARE:

.XX	±0.13 [.005"]
.X	±0.20 [.008"]
X	±0.50 [.019"]
.X°	±1°
X°	±2°

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ANOISON ELECTRONICS LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION COPYRIGHT © 2022 ANOISON ELECTRONICS LTD

ANOISON

TITLE
ATTENUATOR, N MALE TO N FEMALE, 5W, BIDIRECTIONAL, DC-18GHz

VIEW

PART NO. ANO 51-0506-XX

SIZE	SCALE	SHEET	REV.
A3	2.5:1	1/1	A