

MATERIAL & FINISH:

- 1 BODY: BRASS, NICKEL PLATED
- 2 RADIATOR: ALUMINIUM, BLACK


ENVIRONMENTAL DATA:

- 1 TEMPERATURE RANGE: -55°C~+125°C
- 2 2011/65/EU(ROHS) AND 2015/863/(ROHS): COMPLIANT
- 3 1907/2006/EC(REACH) AND 1999/45/EC(REACH): COMPLIANT

ELECTRICAL DATA:

- 1 IMPEDANCE: 50 Ω
- 2 FREQUENCY RANGE: DC-8GHZ
- 3 VSWR: 1.25 MAX.
- 4 AVERAGE POWER: MAXIMUM POWER 50 WATTS AVERAGE TO 25°C AMBIENT TEMPERATURE, DERATED LINEARLY TO 5W @ 125°C
- 5 PEAK POWER: MAXIMUM POWER 500 W (5μS PULSE WIDTH WITH THE MAXIMUM 2% DUTY CYCLE)
- 6 ATTENUATOR ACCURACY: SEE TABLE

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	12/08/22	J. Q



PART NO.	ATTENUATION VALUES & ACCURACY			
	1-10 DB	20 DB	30 DB	40 DB-50DB
ANO 51-5006-XX	±0.5 DB	±0.6 DB	±0.8 DB	±0.8 DB

NOTE: XX REFER TO ATTENUATION VALUE IN DB

DRAWN	W. Y	DATE	12/08/22
CHECKED	X. Y	DATE	12/08/22
APPROVED	J. Q	DATE	12/08/22
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN [] ARE IN INCHES FOR CUSTOMER REFERENCE ONLY UNLESS OTHERWISE SPECIFIED TOLERANCE ARE:		THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ANOISON ELECTRONICS LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION COPYRIGHT © 2022 ANOISON ELECTRONICS LTD	
.XX	±0.13 [0.005"]		
.X	±0.25 [0.010"]		
X	±0.50 [0.019"]		
.X°	±1°		
X°	±2°		



TITLE			
ATTENUATOR N MALE TO N FEMALE 50 WATTS BIDIRECTIONAL, DC-8GHz			
VIEW	PART NO.		
	ANO 51-5006-XX		
SIZE	SCALE	SHEET	REV.
A3	5:1	1/1	A