

4

3

2

1

**MATERIAL & FINISH:**

1 BODY: STAINLESS STEEL, PASSIVATED  
 2 CENTER CONTACT: BERYLLIUM COPPER ALLOY, GOLD PLATED  
 3 SOLDER FERRULE: BRASS, GOLD PLATED  
 4 INSULATOR: PTFE

**ELECTRICAL DATA:**

1 IMPEDANCE: 50 Ω  
 2 FREQUENCY RANGE: DC~18 GHz  
 3 VSWR: 1.30 MAX.

**ENVIRONMENTAL DATA:**

1 TEMPERATURE RANGE: -55 °C~+165 °C  
 2 2011/65/EU (RoHS) AND 2015/863/(RoHS): COMPLIANT  
 3 1999/45/EC (REACH): COMPLIANT

REVISIONS

REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	10/09/21	J QU

CABLE STRIPPING DIMENSIONS

DRAWN	P. CHEN	DATE	10/09/21
CHECKED	X. B. YANG	DATE	10/09/21
APPROVED	J QU	DATE	10/09/21
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN [ ] ARE IN INCHES FOR CUSTOMER REFERENCE ONLY UNLESS OTHERWISE SPECIFIED TOLERANCE ARE:		THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ANOISON ELECTRONICS LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION COPYRIGHT © 2021 ANOISON ELECTRONICS LTD	
.XX	±0.13 [.005"]		
.X	±0.20 [.008"]		
X	±0.50 [.019"]		
.X°	±1°		
X°	±2°		

TITLE  
 N STRAIGHT FEMALE SOLDER FOR IW 2801/GORE 3450/  
 PLEX310 CABLE

VIEW	PART NO. ANO 5112-2336		
	SIZE A3	SCALE 2.5:1	SHEET 1/1
		REV. A	

4

3

2

1