



Construction Specification

	Material	Diameter	
		mm	inch
1. Inner Conductor	Copper Clad Aluminium	2.74	0.108
2. Dielectric	Foam Polyethylene	7.24	0.285
3. Outer Conductor	Bonded Aluminum Foil	7.39	0.291
4. Overall Braid	Tinned Copper	8.13	0.320
5. Jacket	Black Polyethylene	10.29	0.405

Electrical Characteristics

Capacitance	78.4 pF/m	23.9 pF/ft
Impedance(Ω)	50	
Velocity (%)	85	
Inner Conductor DC Resistance(Ω /km)	4.6	
Outer Conductor DC Resistance(Ω /km)	5.4	
Shielding Effectiveness(dB)	>90	

Mechanical Characteristics

Cable Minimum Static Bend Radius	25.4mm	1.00inch
Cable Minimum Dynamic Bend Radius	101.6mm	4.00inch
Weight	0.10 kg/m	.068 lb/ft

Environmental Characteristics

Storage Temp.($^{\circ}$ C)	-70~+85
Installation Temp.($^{\circ}$ C)	-40~+85
Operating Temp($^{\circ}$ C)	-40~+85

Attenuation & Average Power @ 20 $^{\circ}$ C and Sea Level

Frequency(MHz)	Attenuation		Avg.Power(KW)
	dB/100m	dB/100Ft	
30	2.2	0.7	3.33
50	2.9	0.9	2.57
150	5.0	1.5	1.47
220	6.1	1.9	1.20
450	8.9	2.7	0.83
900	12.8	3.9	0.58
1500	16.8	2.1	0.44
1800	18.6	5.7	0.40
2000	19.6	6.0	0.37
2500	22.2	6.8	0.33
3000	24.2	7.4	0.31
5800	35.5	10.8	0.21